

THE UNIVERSITY of EDINBURGH

Edinburgh Research Explorer

Oxygen tolerance capacity of upflow anaerobic solid-state (UASS) with anaerobic filter (AF) system

Citation for published version:

Meng, Y, Jost, C, Mumme, J, Wang, K & Linke, B 2016, 'Oxygen tolerance capacity of upflow anaerobic solid-state (UASS) with anaerobic filter (AF) system', *Journal of Environmental Sciences*, vol. 45, pp. 200-206. https://doi.org/10.1016/j.jes.2016.01.009

Digital Object Identifier (DOI):

10.1016/j.jes.2016.01.009

Link:

Link to publication record in Edinburgh Research Explorer

Document Version: Peer reviewed version

Published In: Journal of Environmental Sciences

General rights

Copyright for the publications made accessible via the Edinburgh Research Explorer is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy The University of Edinburgh has made every reasonable effort to ensure that Edinburgh Research Explorer content complies with UK legislation. If you believe that the public display of this file breaches copyright please contact openaccess@ed.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.



1	Oxygen tolerance capacity of upflow anaerobic solid-state
2	(UASS) with anaerobic filter (AF) system
3	
4	Yao Meng ^{a, b} , Carsten Jost ^b , Jan Mumme ^c , Kaijun Wang ^{a,*} , Bernd Linke ^b
5	
6	^a State Key Joint Laboratory of Environment Simulation and Pollution Control, School
7	of Environment, Tsinghua University, Beijing 100084, PR China
8	^b Department Bioengineering, Leibniz Institute for Agricultural Engineering (ATB),
9	Max-Eyth-Allee 100, 14469 Potsdam, Germany
10	^c UK Biochar Centre, School of GeoSciences, University of Edinburgh, Crew Building,
11	King's Buildings, Edinburgh EH9 3JN, U.K.
12	
13	*Corresponding author. Tel.: +86-010-62789411; fax: +86-010-62793065. E-mail
14	address: wkj@tsinghua.edu.cn

1 Abstract

2 In order to investigate the oxygen tolerance capacity of upflow anaerobic solid-state 3 (UASS) with anaerobic filter (AF) system, the effect of microaeration on thermophilic 4 anaerobic digestion of maize straw was investigated under batch conditions and in the UASS with AF system. Aeration intensities of 0–431 mL O₂ g_{vs}⁻¹ were conducted as 5 6 pretreatment under batch conditions. Aeration pretreatment obviously enhanced anaerobic digestion and an aeration intensity of 431 mL O₂ g_{vs}⁻¹ increased the methane 7 yield by 82.2%. Aeration intensities of $0-355 \text{ mL O}_2 \text{ g}_{vs}^{-1}$ were conducted in the process 8 9 liquor circulation of the UASS with AF system. Dissolved oxygen (DO) of UASS and 10 AF reactors kept around 1.39±0.27 and 0.99±0.38 mg L⁻¹, respectively. pH was 11 relatively stable around 7.11±0.04. Volatile fatty acids (VFAs) and soluble chemical 12 oxygen demand (SCOD) concentration in UASS reactor were higher than those in AF reactor. Methane yield of the whole system was almost stable at 85 ± 7 mL g_{vs}⁻¹ as 13 14 aeration intensity increased step by step. The UASS with AF system showed good 15 oxygen tolerance capacity.

Keywords: Anaerobic digestion; Oxygen tolerance capacity; UASS; Maize straw;
Microaeration; Solid-state.

18 **1** Introduction

Anaerobic digestion (AD) is a promising and competent technology for treating various types of organic wastes and simultaneously producing biogas as a renewable energy carrier (Li et al., 2011). Unavoidable oxygen would be taken into anaerobic digesters unintentionally as the reactors are operated within an aerobic open environment, especially through interactions with the surroundings such as by feeding and mixing

1 (Kato et al., 1997). Some enzyme synthesizing of strict anaerobes can be inhibited and 2 rapid cell lysis of obligatory anaerobic species can occur in the presence of oxygen so 3 that oxygen is thought to be an inhibitor to anaerobic process (Botheju and Bakke, 4 2011). Methanogens will be inhibited by oxygen in anaerobic digesters (Ren and Wang, 5 2004). On the other hand, the rate-limiting step, hydrolysis of particulate matter in AD 6 can be enhanced (Ramos and Fdz-Polanco, 2013) because oxygen can promote 7 facultative microorganisms excrete a higher amount of enzymes hydrolysis (Johansen 8 and Bakke, 2006; Sheets et al., 2015) and limited aeration could increase synthesis and 9 activity of cellular hydrolytic enzymes (Zhu et al., 2009). Lim and Wang (2013) 10 reported that microaerobic treatment could reduce the formation of toxic metabolites 11 (e.g. lactic acid and ethanol) as well as promote the synthesis of certain lipids required 12 for the stability of anaerobes cell membrane. Previous studies about microaeration 13 pretreatment were conducted under batch conditions (Charles et al., 2009; Mshandete et 14 al., 2005). However, the effect of oxygen on anaerobic digestion under semi-continuous 15 conditions was still unclear.

A UASS with AF system was first described by Mumme et al. (2010), and worked well with maize silage (Mumme et al., 2010), wheat straw (Pohl et al., 2012; Pohl et al., 2013), horse manure (Böske et al., 2014; Böske et al., 2015), and maize straw (Meng et al., 2016). Different from other anaerobic reactors, this system included a UASS reactor in which solid feedstock was digested in a plug-flow mode and an AF reactor in which most methanogens existed as biofilm. The effect of oxygen on anaerobic digestion in UASS and AF system can not be predicted from performance data of other reactors.

23 Therefore, the overall aim of this research is to investigate the oxygen tolerance

24 capacity of the UASS with AF system. Further aims are to investigate the effect of

microaeration on maize straw anaerobic digestion under batch conditions; to investigate
 the effect of oxygen on maize straw anaerobic digestion in two-stage semi-continuous
 reactors.

4 2 Materials and Methods

5 2.1 Substrates and inoculum properties

Maize straw was collected from a farm in Cadenberge, Germany. After harvest, the
straw was chopped to a final average cutting length of 2–5 cm. Afterwards, it was airdried to achieve a moisture content of less than 10% and stored at room temperature in a
woven bag prior to the experiment.

10 The inoculum was obtained from previous biogas experiments, which were incubated

11 under thermophilic $(55^{\circ}C)$ conditions at the Leibniz Institute for Agricultural

12 Engineering (ATB). The inoculum were stored at room temperature for several months

13 without feeding, in order to remove biodegradable chemical oxygen demand (COD). It

14 was removed from solids with a sieve of 1 mm before inoculating. Detailed properties

15 of substrates and inoculum are presented in Table 1.

16 2.2 Batch experiments setup

17 5 experimental treatments were labelled as B1–B5. Glass bottles (capacity 1 L) were

18 filled with 900 g of inoculum. 11.34 g straw was added in each bottle so that the initial

19 VS ratio of substrates to inoculum was kept at 1:2. All the bottles were placed in an

20 incubator (55 $^{\circ}$ C) without stirring. Afterwards, a peristaltic pump (air flow: 7 mL min⁻¹)

21 with air stone was used to aerate the treatments B1–B5 and the different aeration

22 intensities of B1-B5 are shown in Table 2. After 0–2 days of aeration, the bottles were

immediately sealed and connected to gas collecting tubes to conduct anaerobic
digestion. The controls (without straw) were run in duplicates and the treatments in
triplicates. The anaerobic digestion last 59 days until daily biogas yield of each bottle
was less than 1% of the total cumulated biogas yield as stated in the VDI guideline 4630
(VDI, 2006). Methane fraction was analyzed from time to time according to produced
biogas yield which were enough for biogas analyzer GA 2000 (ansyco GmbH
Germany) to measure.

8 2.3 The UASS with AF system setup and operation

9 A modification of the UASS with AF system described by Mumme et al. (2010) was 10 used in this work. The schematic of the system is shown in Fig. 1. The straw was fed 11 manually through an inclined feeding pipe to the bottom of the UASS reactor, ascended 12 in the form of a solid-state bed (SSB) in the reactor and was removed manually from the 13 top by removing the reactor's lid as described previously (Pohl et al., 2012) so that the 14 reactor was named upflow anaerobic solid-state reactor. According to previous 15 operation experience (Pohl et al., 2012; Böske et al., 2014), the digestates compact can 16 lead to clogging and can interfere with liquor circulation (Mumme et al., 2010). 17 Therefore, the liquor flow inside the UASS reactor was changed from upflow to 18 downflow in this work. The process liquor was applied via the lid of the UASS reactor, 19 passed through the solid-state bed of the straw, and was removed from the bottom of the 20 reactor.

To relieve the inhibition of accumulated VFAs, an additional AF reactor was added
after the UASS reactor to form a two-stage system. The AF reactor was filled with PE

23 biofilm carriers (Bioflow 40, RVT Process Equipment GmbH, Germany) with a surface

1	area of 305 m ^{2} m ^{-3} . The process liquor in AF was upflow. The working volume of the
2	UASS reactor, the AF reactor and buffer tank was 35 L, 35 L and 8 L each. Process
3	liquor circulation of both system was set to a flow rate of 11.7 L h^{-1} using peristaltic
4	pumps (Heidolph, Germany). Both UASS and AF reactors were heated via a
5	thermostatically controlled water jacket (Lauda, Lauda-Königshofen, Germany).
6	Aeration was conducted in the buffer tank for process liquor from the AF reactor using
7	an aeration pump and an air stone. Two drum-type gas meters (TG05/5 Ritter,
8	Germany) were used to measure the biogas production of the UASS and AF reactor. A
9	combined pH-temperature-probe (InPro4260, Mettler-Toledo, USA) was equipped to
10	AF reactor (at effluent outlet) for continuous online measurement. Maize straw was fed
11	daily at an organic loading rate (OLR) of 4.5 $g_{vs} L_{UASS}^{-1} d^{-1}$ from the feeding pipe and
12	the digestates were removed from the top of the UASS reactors every 5 days. After the
13	digestates being removed, a volume of about 9.4 L (height: 20 cm) of solid organic
14	matter remained in the UASS reactor. The solid retention time (SRT) was about 9.7
15	days. After the biogas production became stable, the system was operated for 50 days
16	meanwhile the UASS reactors were operated at five different aeration intensities as
17	shown in Table 2.

18 2.4 Analytical methods

The biogas composition of each reactor was measured every day using an industrial
biogas analyzer (SSM 6000, Pronova, Germany). The DO of effluent of both reactors
were measured with a DO meter (Hanna 9147, USA). The determination of total solids
(TS) and volatile solids (VS) was conducted according to DIN standard methods (DIN,
2001). Neutral detergent fiber (NDF), acid detergent fiber (ADF), and acid detergent

1	lignin (ADL) were analyzed by a fiber analyzer (ANKOM2000, USA) as described in
2	the literature (Van Soest et al., 1991). Total ammonium nitrogen (TAN) was analyzed
3	according to the VDLUFA method (VDLUFA, 2007). Total Kjeldahl nitrogen (TKN)
4	and chemical oxygen demand (COD) were measured according to DIN EN 25663:
5	1993-11 and DIN ISO 15705: 2003-01 respectively. Total carbon (TC) and total
6	nitrogen (TN) were determined by elemental analysis (DIN EN 15104: 2011-04).
7	Volatile fatty acids were measured with a gas-phase chromatograph (Agilent GC
8	7890A, USA) equipped with a Permabond-FFAP column (length 30 m, diameter
9	0.32 mm, film thickness 0.5 $\mu m)$ and a flame ionization detector. C, N, S, and H
10	fractions were analyzed with a vario EL III elemental analyzer (Elementar
11	Analysensysteme GmbH, Germany), but had only been available for solid samples. For
12	the BMP batch digestion tests, the composition of the produced biogas (CH_4 and CO_2)
13	was analyzed using the portable gas analyzer GA 2000 (Ansyco GmbH, Germany)
14	equipped with infrared detectors.
15	2.5 Calculations
16	The calculation of equivalent aerated O ₂ intensity of the batch experiment is shown as
17	Eq. (1).

18
$$I_b = Q \cdot \varphi \cdot t \cdot f/(\mathbf{m} \cdot \mathbf{TS} \cdot \mathbf{VS})$$
 (1)

In Eq. (1), I_b is the equivalent aerated O₂ intensity of the batch experiment. *Q* is the air flow (7 mL min⁻¹). φ is the O₂ volume content in air (21%). *t* and *f* are the corresponding aeration time and aeration pump working frequency of each treatment (Table 2). m is the straw amount added in each treatment (11.34 g). TS and VS is the total solids and volatile solids of straw shown in Table 1. The calculation of equivalent aerated O₂ intensity of the two-stage system is shown as
 Eq. (2).

3
$$I_t = Q \cdot \varphi \cdot f / (OLR \cdot V)$$
 (2)

In Eq. (2), I_t is the equivalent aerated O₂ intensity of the two-stage system. Q and f are the corresponding air flow and aeration pump working frequency of each regime (Table 2). φ is the O₂ volume content in air (21%). OLR is the organic loading rate of the twostage system (4.5 g_{vs} L_{UASS}⁻¹ d⁻¹). V is the working volume of the UASS reactor (35L).

8 The measured biogas volume was converted to its volume at standard temperature,

9 standard pressure, and dry conditions according to VDI guideline 4630 (VDI, 2006). Air

10 was introduced each time when feeding and when removing digestates, which would

11 potentially disrupt the biogas composition analysis. Therefore, the methane yield was

12 calculated on the assumption that the volumetric fractions of methane and carbon

13 dioxide sum up close to 100% as recommended in VDI guideline 4630 (VDI, 2006).

14 Each of the two measured values was multiplied by the same factor so that the sum of

15 the two corrected measured values was 100% neglecting trace gases. The detailed

16 calculation was previously described by Böske et al. (2014).

17 **3** Results and discussion

18 3.1 Impact of microaeration under batch digestions

The inoculum used was found to be in good condition, as the cellulose reference yielded $600 \pm 23 \text{ mL g}_{vs}^{-1}$ under thermophilic condition was in accordance with the lower limit stated in the VDI guideline 4630 (VDI, 2006). Biogas yields were calculated from the first day of AD until daily biogas yield was less than 1% of the cumulative biogas yield

1	as stated in the VDI guideline 4630 (VDI, 2006). As shown in Fig. 2a, the biogas yields
2	increased sharply in the first ten days. The start of biogas production was more intensive
3	for the aerated treatments (B2–B5) than the unaerated treatment (B1). This is because
4	aeration enhanced the hydrolysis process of maize straw and increased the concentration
5	of readily available metabolites inside the fermentation bottles compared to the control
6	without aeration. Acidogenesis and methanogenesis reaction rate were higher in the first
7	several days because of higher reactant concentration during the anaerobic step. The
8	result was constant with cumulative methane yield of microaeration pretreatment of
9	maize straw reported by Fu et al. (2015). Díaz et al. (2010) also reported that
10	microaeration pretreatment can reduce the lag-phase time of sludge anaerobic digestion.
11	The methane fraction increased step by step as shown in Fig. 2b. The overall methane
12	fraction of B1-B5 was 70 \pm 3%, 70 \pm 1%, 73 \pm 1%, 72 \pm 1%, and 73 \pm 1%. Methane is
13	produced only during the methanogenesis process which was the third step after
14	hydrolysis and acidogensis process (Meng et al., 2016). Most reactions just after
15	aeration in this experiment were hydrolysis and acidogensis so that methane fraction
16	increased step by step as the experiment went on. The cumulative methane yield of B1-
17	B5 was 152 \pm 35, 193 \pm 12, 219 \pm 21, 248 \pm 20, and 277 \pm 11 mL g _{vs} -1. The maximum
18	cumulative methane yield was achieved at the equivalent aerated O ₂ intensity of 431 mL
19	g_{vs}^{-1} (B5), which was 82.2% higher than that of untreated treatment. It was followed by
20	the equivalent aerated O_2 intensity of 216 (B4), 108 (B3), and 54 (B2) mL g_{vs}^{-1} , which
21	62.3%, 44.1%, and 27.0% higher than that of untreated treatment, respectively. This is
22	due to improved degradation of maize straw and growth of methanogenic bacteria (Ahn
23	et al., 2014). In the research of Fu et al. (2015), methane yield of maize straw was
24	improved by 16.24%. Lim and Wang (2013) also found that limited air addition did not

inhibit the strictly anaerobic methanogens during co-digestion of brown water and food
 waste and actually enhanced methane yield by 21%.

3 3.2 Impact of microaeration under two-stage conditions

DO and pH in the reactors were shown in Fig. 3. Average DO of both UASS and AF 4 5 reactors of the 5 regimes nearly did not change although aeration intensity was 6 increased. This indicates that UASS with AF system has strong oxygen tolerance 7 capacity. The process liquor containing dissolved oxygen firstly passed though solid-8 state bed in the UASS reactor and then the AF reactor. Oxygen was firstly consumed by 9 facultative microorganisms in the UASS reactor and then by the facultative 10 microorganisms in the biofilm in the AF reactor (Song and Logan, 2004). Therefore, the 11 average DO of effluent of AF reactor (0.99±0.38 mg L⁻¹) was lower than that of the 12 effluent of the UASS reactor $(1.39\pm0.27 \text{ mg L}^{-1})$. The facultative microorganisms in 13 both reactor provided oxygen tolerance capacity potential of anaerobic digesters such as 14 the UASS and AF reactor. pH was relatively stable around 7.11±0.04 during all the 15 experiment periods which was suitable for anaerobic digestion (Liu et al., 2008). 16 VFAs and SCOD concentration in process liquor were shown in Fig. 4. In regime 3 (equivalent aerated O_2 intensity=89 mL g_{vs}^{-1}), both VFAs and SCOD concentration 17 18 were lower than those of the other 4 regimes. VFAs and SCOD concentration of regime 19 4 and 5 were higher than regime 3 but still lower than regime 1 and 2. VFAs are the 20 process products in anaerobic digestion, which are necessary for the biogas production. 21 VFAs concentration is also an indicative mark of the working condition of anaerobic 22 process (Li et al., 2014). Compared between UASS and AF reactors, VFAs and SCOD 23 had the similar trend because the hydrolytic retention time (HRT) of process liquor in

1	UASS or AF reactor was only 3 hours which was short enough for adequate mixing in							
2	both reactors. Both average VFAs and SCOD concentration in UASS reactor were							
3	higher than those of AF reactor. As aeration intensity increased from regime 1 to regime							
4	3, the whole anaerobic process was enhanced so that VFAs and SCOD concentration							
5	were the lowest (Fig. 4) and methane yield of AF was the highest (Fig. 6) in the 5							
6	regimes. As aeration intensity increased from regime 3 to regime 5, inhibition of							
7	methanogenesis in the UASS reactor by oxygen became more obvious. At the same							
8	time, Ahn et al. (2014) pointed that soluble chemical oxygen demand (SCOD) could be							
9	increased through aeration in the research of sewage sludge. Therefore, the VFAs and							
10	SCOD concentration increased from regime 3 to regime 5. Similarly, because of the							
11	conversion of VFAs and SCOD in AF, the VFAs and SCOD concentration gap between							
12	UASS and AF reactors got larger from regime 1 to regime 5 as shown in Fig. 4. The							
13	average VS, COD, cellulose and hemi-cellulose contents of the digestages were $86.9\pm$							
14	6.0%, 1147.0 \pm 68.9%, 39.5 \pm 4.0%, and 29.0 \pm 3.0%, which were almost stable as							
15	aeration intensity increased.							
1.6								
10	3.3 Oxygen tolerance capacity of UASS with AF system							
17	Daily methane production rate and methane yield of the five regimes are shown in Fig.							
18	5 and Fig. 6. Daily methane production rate showed a periodic pattern influenced by the							

19 removal of solid residue every five days. Average methane production rate and methane

20 $\,$ yield of the five regimes had the same trend as OLR was kept constantly at 4.5 g_{vs}

21 $L_{UASS}^{-1} d^{-1}$. Methane yield of the UASS reactor decreased by 26.8% from 54±10 to 40±7

- 22 mL g_{vs}^{-1} slightly as aeration intensity increased from Regime 1 to Regime 3. Methane
- 23 yield of the UASS reactor almost kept the same as aeration intensity increased from

1	Regime 3 to Regime 5. Methane yield in AF kept almost constant between 38±5 and
2	47±8 mL g_{vs}^{-1} . Meanwhile it increased the maximum to 47±8 mL g_{vs}^{-1} in regime 3 at an
3	equivalent aerated O_2 intensity of 89 mL $O_2 g_{vs}^{-1}$. The total methane yield of the whole
4	system was relatively stable at 85 ± 7 mL g_{vs}^{-1} . Methane fraction of UASS reactor was
5	around $63\pm2\%$ while methane fraction of AF reactor increased from $63\pm1\%$ to $68\pm1\%$.
6	The methane production rate and methane yield of both UASS and AF reactor were not
7	influenced significantly although aeration intensity increased step by step. This is
8	because facultative hydrolysis microorganisms in UASS reactor and biofilm in AF
9	reactor can relieve the inhibition from oxygen (Shen and Guiot, 1996).

10 4 Conclusions

Aeration pretreatment with an equivalent aeration intensity of 431 mL O₂ g_{vs}⁻¹ improved methane yield by 82.2%. Aeration pretreatment can enhance methane production of maize straw under batch conditions. Two stage-system showed relative stability as aeration intensity increased. Although methane yield of the UASS and AF reactor were affected by aeration, the total methane yield of the whole system was relatively stable. The UASS with AF system showed high oxygen tolerance capacity.

17 Acknowledgements

This collaborative research received funding from the German Federal Ministry of
Education and Research (No. 03SF0381A), National Natural Science Foundation of
China (No.21206084), and the National Key Technology Support Program of China
(2014BAC27B01). Additionally, the authors would like to thank Ulf Lüder and Laureen
Herklotz for their technical and analytical support.

References

3	1. Ahn, Y., Wi, J., Park, J., Higuchi, S., Lee, N., 2014. Effects of Pre-aeration on the
4	Anaerobic Digestion of Sewage Sludge. Environ. Eng. Res. 19, 59-66.
5	2. Böske, J., Wirth, B., Garlipp, F., Mumme, J., Van den Weghe, H., 2014. Anaerobic
6	digestion of horse dung mixed with different bedding materials in an upflow solid-state
7	(UASS) reactor at mesophilic conditions. Bioresource Technol. 158, 111-118.
8	3. Böske, J., Wirth, B., Garlipp, F., Mumme, J., Van den Weghe, H., 2015. Upflow
9	anaerobic solid-state (UASS) digestion of horse manure: Thermophilic vs. mesophilic
10	performance. Bioresource Technol. 175, 8-16.
11	4. Botheju, D., Bakke, R., 2011. Oxygen effects in anaerobic digestion-a review. The
12	Open Waste Manage. 4, 1-19.
13	5. Charles, W., Walker, L., Cord-Ruwisch, R., 2009. Effect of pre-aeration and
14	inoculum on the start-up of batch thermophilic anaerobic digestion of municipal solid
15	waste. Bioresource Technol. 100, 2329-2335.
16	6. Díaz, I., Lopes, A.C., Pérez, S.I., Fdz-Polanco, M., 2010. Performance evaluation of
17	oxygen, air and nitrate for the microaerobic removal of hydrogen sulphide in biogas
18	from sludge digestion. Bioresource Technol. 101, 7724-7730.
19	7. DIN, 2001. Chemical Analyses — Determination of loss on ignition in sediment,
20	sludge, soil, and waste. Deutsches Institut für Normung (DIN), Beuth Verlag, Berlin.

- 1 8. Fu, S., Wang, F., Yuan, X., Yang, Z., Luo, S., Wang, C., Guo, R., 2015. The
- 2 thermophilic (55°C) microaerobic pretreatment of corn straw for anaerobic digestion.
- 3 Bioresource Technol. 175, 203-208.
- 9. Johansen, J.E., Bakke, R., 2006. Enhancing hydrolysis with microaeration. Water
 Sci. Technol. 53, 43-50.
- 6 10. Kato, M.T., Field, J.A., Lettinga, G., 1997. Anaerobic tolerance to oxygen and the
 7 potentials of anaerobic and aerobic cocultures for wastewater treatment. Braz. J. Chem.
 8 Eng. 14.
- 9 11. Li, W., Zhang, G., Zhang, Z., Xu, G., 2014. Anaerobic Digestion of Yard Waste
- 10 with Hydrothermal Pretreatment. Appl. Biochem. Biotech. 172, 2670-2681.
- 11 12. Li, Y., Park, S.Y., Zhu, J., 2011. Solid-state anaerobic digestion for methane
- 12 production from organic waste. Renew. Sust. Energ. Rev. 15, 821-826.
- 13 13. Lim, J.W., Wang, J., 2013. Enhanced hydrolysis and methane yield by applying
- 14 microaeration pretreatment to the anaerobic co-digestion of brown water and food
- 15 waste. Waste Manage. 33, 813-819.
- 16 14. Liu, C., Yuan, X., Zeng, G., Li, W., Li, J., 2008. Prediction of methane yield at
- 17 optimum pH for anaerobic digestion of organic fraction of municipal solid waste.
- 18 Bioresource Technol. 99, 882-888.
- 19 15. Meng, Y., Jost, C., Mumme, J., Wang, K., Linke, B., 2016. An analysis of single
- 20 and two stage, mesophilic and thermophilic high rate systems for anaerobic digestion of
- 21 corn stalk. Chem. Eng. J. 288, 79-86.

1	16. Meng, Y., Mumme, J., Xu, H., Wang, K., 2016. A biologically inspired variable-pH
2	strategy for enhancing short-chain fatty acids (SCFAs) accumulation in maize straw
3	fermentation. Bioresource Technol. 201, 329-336.
4	17. Mshandete, A., Björnsson, L., Kivaisi, A.K., Rubindamayugi, S.T., Mattiasson, B.,
5	2005. Enhancement of anaerobic batch digestion of sisal pulp waste by mesophilic
6	aerobic pre-treatment. Water Res. 39, 1569-1575.
7	18. Mumme, J., Linke, B., Tölle, R., 2010. Novel upflow anaerobic solid-state (UASS)
8	reactor. Bioresource Technol. 101, 592-599.
9	19. Pohl, M., Heeg, K., Mumme, J., 2013. Anaerobic digestion of wheat straw -
10	Performance of continuous solid-state digestion. Bioresource Technol. 146, 408-415.
11	20. Pohl, M., Mumme, J., Heeg, K., Nettmann, E., 2012. Thermo- and mesophilic
12	anaerobic digestion of wheat straw by the upflow anaerobic solid-state (UASS) process.
13	Bioresource Technol. 124, 321-327.
14	21. Ramos, I., Fdz-Polanco, M., 2013. The potential of oxygen to improve the stability
15	of anaerobic reactors during unbalanced conditions: Results from a pilot-scale digester
16	treating sewage sludge. Bioresource Technol. 140, 80-85.
17	22. Ren, N.Q., Wang, A.J., 2004. Anaerobic Biotechnology Principles and Applications.
18	Chemical Industry Press, Beijing.
19	23. Sheets, J.P., Ge, X., Li, Y., 2015. Effect of limited air exposure and comparative
20	performance between thermophilic and mesophilic solid-state anaerobic digestion of

21 switchgrass. Bioresource Technol. 180, 296-303.

1	24 Shan C.E. Guiat S.B. 1006 Lang term impact of dissolved O2 on the activity of
1	24. Shen, C.F., Gulot, S.K., 1990. Long-term impact of dissolved O2 on the activity of
2	anaerobic granules. Biotechnol. Bioeng. 49, 611620.
2	
3	25. Song, Y., Logan, B.E., 2004. Effect of O2 exposure on perchlorate reduction by
4	Dechlorosoma sp. KJ. Water Res. 38, 1626-1632.
5	26. Van Soest, P.J., Robertson, J.B., Lewis, B.A., 1991. Methods for dietary fiber,
6	neutral detergent fiber, and nonstarch polysaccharides in relation to animal nutrition. J.
7	Dairy Sci 74 3583-97
8	27. VDI 4630, 2006. Fermentation of organic materials: characterization of the
9	substrate, sampling, collection of material data, fermentation tests. In: Verein Deutscher
10	In conjune (Ed.) VDI Handhuch Energistechnik, Douth Varley, Darlin
10	ingemeure (Ed.), VDI-Handbuch Energietechnik, Beuth Verlag, Bernn.
11	28. VDLUFA, 2007. Method Book III-The Chemical Analysis of Feedstuffs, third ed.,
10	including 1st 7th Supplement Delivery 1082 2007 1076 2007
12	including 1st-/th Supplement Derivery 1983-2007, 1976-2007.
13	29. Zhu, M., Lü, F., Hao, L., He, P., Shao, L., 2009. Regulating the hydrolysis of
1 /	anomic works hy might constinue and offly out residentian Waste Manage 20, 2042
14	organic wastes by micro-aeration and effluent recirculation. Waste Manage. 29, 2042-
15	2050.
16	

1 Figure Captions

- 2 Fig. 1 Schematic of the system under semi-continuous conditions. (UASS: upflow
- 3 anaerobic solid-state reactor; AF: anaerobic filter reactor; Pump1: Liquor circulation
- 4 pump; Pump 2: Aeration pump; working volume of the UASS reactor, AF reactor, and
- 5 Buffer tank were 35, 35, and 8L, respectively.)
- 6 Fig. 2 Properties of biogas in the batch experiment. (a: cumulative biogas yield; b:
- 7 methane fraction; equivalent aerated O_2 intensity of B1–5 are 0, 54, 108, 216, and 431

8 mL g_{vs}^{-1} , respectively.)

- 9 Fig. 3 pH and dissolved oxygen (DO) of process liquor of upflow anaerobic solid-state
- 10 (UASS) with anaerobic filter (AF) system.
- 11 Fig. 4 VFAs and SCOD concentration of process liquor of upflow anaerobic solid-
- 12 state (UASS) with anaerobic filter (AF) system.
- 13 Fig. 5 Methane production rate of the upflow anaerobic solid-state (UASS) and
- 14 anaerobic filter (AF) reactor.
- 15 Fig. 6 Methane yield of the upflow anaerobic solid-state (UASS) and anaerobic filter16 (AF) reactor.

1 Figures



Fig. 1 - Schematic of the system under semi-continuous conditions. (UASS: upflow
anaerobic solid-state reactor; AF: anaerobic filter reactor; Pump1: Liquor circulation
pump; Pump 2: Aeration pump; working volume of the UASS reactor, AF reactor, and
Buffer tank were 35, 35, and 8L, respectively.)



Fig. 2 – Properties of biogas in the batch experiment. (a: cumulative biogas yield; b:
methane fraction; equivalent aerated O₂ intensity of B1–5 are 0, 54, 108, 216, and 431
mL g_{vs}⁻¹, respectively.)



Fig. 3 - pH and dissolved oxygen (DO) of process liquor of upflow anaerobic solid-state
(UASS) with anaerobic filter (AF) system.



2 Fig. 4 - VFAs and SCOD concentration of process liquor of upflow anaerobic solid-

3 state (UASS) with anaerobic filter (AF) system.



Fig. 5 - Methane production rate of the upflow anaerobic solid-state (UASS) and
anaerobic filter (AF) reactor.



2 Fig. 6 - Methane yield of the upflow anaerobic solid-state (UASS) and anaerobic filter

3 (AF) reactor.

1 **Table Captions**

- 2 Table 1 Properties of substrates and inoculum used in the experiments.
- 3 Table 2 Aeration intensity of the batch experiment and the two-stage system

1 Tables

Parameter	Unit	Maize straw	Inoculum
TS	%FM	92.4	3.1
VS	%TS	93.8	70.7
COD	g kg ⁻¹	1106	38
Ν	%TS	0.56	4.16
С	%TS	46.51	41.30
S	%TS	0.08	0.50
Н	%TS	6.89	6.88
TP	mg kg ⁻¹ FM	810.5	355.7
TAN	mg kg ⁻¹ FM	N.D.	1250
TKN	mg kg ⁻¹ FM	N.D.	2493
Crude fat	%TS	0.8	N.D.
Crude fiber	%TS	42.9	N.D.
NDF	%TS	85.3	N.D.
ADF	%TS	50.3	N.D.
ADL	%TS	7.3	N.D.

2 Table 1 - Properties of substrates and inoculum used in the experiments.

Note: TS (total solids), VS (volatile solids), COD (chemical oxygen demand), TP (total phosphorus), TAN (total ammonium nitrogen), TKN (total Kjeldahl nitrogen), NDF (neutral detergent fiber), ADF (acid detergent fiber), ADL (acid detergent lignin). N.D. Not Determined 3 4 5 6 7

Batch experiments				Two-stage system				
Treat ments	Aeration time*	Aeration pump working frequency	Equivalent aerated O ₂ intensity	Experime nt period	Experiment time	Aeration air flow rate	Aeration pump working frequency	Equivalent aerated O ₂ intensity
	hour		mL g_{vs} -1		day	mL min ⁻¹		mL O ₂ g_{vs} -1
B1	0	0	0	Regime 1	1-10	0	0	0
B2	24	15/60min**	54	Regime 2	11-20	47	15/60min	23
B3	48	15/60min	108	Regime 3	21-30	185	15/60min	89
B4	48	30/60min	216	Regime 4	31-40	185	30/60min	178
B5	48	60/60min	431	Regime 5	41-50	185	60/60min	355

1 Table 2 – Aeration intensity of the batch experiment and the two-stage system

2 3 4

* Pre-aeration directly before start of the AD experiment
** This means aeration pump worked for 15 min every 60 min (15 min on, 45 min off).