THE UNIVERSITY *of* EDINBURGH

Edinburgh Research Explorer

Replicated Computations Results (RCR) Report for “Semantics and Efficient Simulation Algorithms for an Expressive Multi-Level Modeling Language”

Citation for published version:

Hillston, J 2017, 'Replicated Computations Results (RCR) Report for “Semantics and Efficient Simulation Algorithms for an Expressive Multi-Level Modeling Language”', *ACM Transactions on Modeling and Computer Simulation*. <https://doi.org/10.1145/3055539>

Digital Object Identifier (DOI):

[10.1145/3055539](https://doi.org/10.1145/3055539)

Link:

[Link to publication record in Edinburgh Research Explorer](#)

Document Version:

Peer reviewed version

Published In:

ACM Transactions on Modeling and Computer Simulation

General rights

Copyright for the publications made accessible via the Edinburgh Research Explorer is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

The University of Edinburgh has made every reasonable effort to ensure that Edinburgh Research Explorer content complies with UK legislation. If you believe that the public display of this file breaches copyright please contact openaccess@ed.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.

Replicated Computations Results (RCR) Report for “Semantics and Efficient Simulation Algorithms for an Expressive Multi-Level Modeling Language”

JANE HILLSTON, University of Edinburgh

“Semantics and Efficient Simulation Algorithms on an Expressive Multi-Level Modelling Language”, by Helms *et al.* presents new work on the domain-specific modelling and simulation language ML-Rules [3]. For the first time the language is given a formal semantics which establishes the relationship between the language and its underlying mathematical model, continuous time Markov chains. Furthermore subclasses of the language are identified for which it is possible to specify and implement more efficient approaches to simulation. These new algorithms are demonstrated on substantial case studies. This replicated computation report focusses on the ML-Rules modelling tool, and specifically the new algorithms as demonstrated in the case studies in the paper [1]. The software was straightforward to install and use and the experimental results from the paper could all be reproduced.

CCS Concepts: •Computer systems organization → Embedded systems; Redundancy; Robotics; •Networks → Network reliability;

Additional Key Words and Phrases: RCR report, formal semantics, efficient simulation algorithms, systems biology

ACM Reference format:

Jane Hillston. 2010. Replicated Computations Results (RCR) Report for “Semantics and Efficient Simulation Algorithms for an Expressive Multi-Level Modeling Language”. *ACM Trans. Model. Comput. Simul.* 9, 4, Article 39 (March 2010), 3 pages.
DOI: 0000001.0000001

1 INTRODUCTION

The ML-Rules modelling and simulation language is well-established and supported by a fairly mature software toolkit [4]. Nevertheless the replication of the results of this paper took place in two stages. Firstly the ML-Rules tool was downloaded and installed and its functionality was investigated in a general sense. In the second stage the focus was explicitly on the results presented in the paper [1], “Semantics and Efficient Simulation Algorithms of an Expressive Multi-Level Modeling Language”. This work was supported by the authors as, in addition to running the models through the ML-Rules software, it was necessary to also to run the results through R scripts in order to create that plots that could be compared to the results in the paper. The authors provided appropriate scripts, allowing the evaluator to conduct the experiments in ML-Rules and the R processing, and these scripts were made available in the ML-Rules repository

Author’s address: J. Hillston, School of Informatics, University of Edinburgh, Edinburgh, Scotland, UK; email: jane.hillston@ed.ac.uk.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

© 2009 Copyright held by the owner/author(s). Publication rights licensed to ACM. XXXX-XXXX/2010/3-ART39 \$15.00
DOI: 0000001.0000001

(<https://git.informatik.uni-rostock.de/mosi/mlrules2>). This approach to result replication is similar to the approach taken in the previous RCR report by Luck [2].

2 REPLICATION OF COMPUTATION RESULTS

2.1 Installation of ML-Rules tool

The ML-Rules software suite is already well-developed and is supported by a comprehensive and clear website. This repository contains not only the source code for the tool, and instructions for its installation, but also a sizeable collection of example models, grouped around the publications in which they appear. Downloading the software and installing it was straightforward and proceeded without any problems. Several simple example models were then explored to check that the functionality of the tool is as represented in the paper. This proved to be the case and the tool was intuitive to use both for editing and running models.

2.2 Repeating the Results from the paper

For the purposes of this replication report the focus was on the version of the ML-Rules tool corresponding to the paper [1]. The corresponding entry in the repository [4] provides the models which are used in the three presented case studies, the R scripts needed to create the plots and results as shown in the paper, as well as all the necessary software. Indeed each experiment has been packaged as a .jar file.

In the paper three case studies are presented and all three were scrutinised for this replication report. The first study considers the Wnt/ β -catenin pathway, which has been shown to play an important role in cell differentiation and the development of cancer. The ML-Rules model developed in this case is shown to satisfy the characterisation of the M_{static} subclass identified in the paper (its spatial compartmental structure does not change over the course of an execution of the model) allowing it to take advantage of the corresponding Static Simulator. The replication followed the same experimental settings as described in the paper — 100 replications of each parameter setting until simulation time 300. The results reported in Section 7.1 of the paper were reproduced without any problems.

The second case study in the paper considers a less restrictive class of models, where only some rules can be considered as static with respect to the compartmentalisation. This scheme is termed hybrid and the example considered in the paper relates to the unicellular organism *Dictyostelium discoideum* amoeba, commonly referred to as “slime mold”. This model captures both the intracellular chemical reactions and the physical movement (in a grid) of the amoebae, investigating the formation of a multicellular “slug” which occurs in some circumstances. This uses the Hybrid Simulator. Again the replication followed the same experimental settings as described in the paper — 20 simulation replications, each until simulation time 5000. The number of amoeba cells present was varied across the experiments and the objective was to investigate the formation of slugs. Considerable computational effort was needed but nevertheless the results reported in Section 7.3 of the paper were replicated.

The final case study of the paper presents a model in which the dynamic formation and dissolution of networks of mitochondria is investigated. In particular the model probes the influence of fission protein on mitochondrial structure and health. This model falls into the subclass M_{bind} , and the execution of the model takes advantage of the corresponding algorithm. The replication followed the same experimental settings as described in the paper — 20 replications of each experiment setting until simulation time 100. The results obtained were indistinguishable to those presented in the paper.

ACKNOWLEDGMENTS

The author would like to thank Dr. Tobias Helms of the University of Rostock for providing access to the appropriate scripts in the ML-Rules repository.

REFERENCES

- [1] Tobias Helms, Tom Warnke, Carsten Maus, and Adelinde M. Uhrmacher. 2017. Semantics and Efficient Simulation Algorithms of an Expressive Multi-Level Modeling Language. *Transactions on Modeling and Computer Simulation* to appear (2017).
- [2] Alexander Lück. 2016. Replicated Computational Results (RCR) Report for "Automatic Moment-Closure Approximation of Spatially Distributed Collective Adaptive Systems". *Transactions on Modeling and Computer Simulation* 26, 4 (March 2016), 27:1–27:3.
- [3] Carsten Maus, Stefan Rybacki, and Adelinde M. Uhrmacher. 2011. Rule-based multi-level modeling of cell biological systems. *BMC Systems Biology* 5, 166 (2011). DOI : <http://dx.doi.org/10.1186/1752-0509-5-166>
- [4] University of Rostock. 2017. ML-Rules Repository. <https://git.informatik.uni-rostock.de/mosi/mlrules2>. (2017). accessed 05/01/2017.

Received January 2017