



THE UNIVERSITY *of* EDINBURGH

Edinburgh Research Explorer

## Thermo-electro-mechanical characterisation of 3D printed multifunctional materials

### Citation for published version:

Delbart, R, Papasavvas, A, Robert, C, Truong Hoang, T-Q & Martinez-Hergueta, F 2022, 'Thermo-electro-mechanical characterisation of 3D printed multifunctional materials', 18th European Mechanics of Materials Conference, Oxford, United Kingdom, 4/04/22.

### Link:

[Link to publication record in Edinburgh Research Explorer](#)

### General rights

Copyright for the publications made accessible via the Edinburgh Research Explorer is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

### Take down policy

The University of Edinburgh has made every reasonable effort to ensure that Edinburgh Research Explorer content complies with UK legislation. If you believe that the public display of this file breaches copyright please contact [openaccess@ed.ac.uk](mailto:openaccess@ed.ac.uk) providing details, and we will remove access to the work immediately and investigate your claim.



## Thermo-electro-mechanical characterisation of 3D printed multifunctional materials

R. Delbart<sup>1</sup>, A. Papasavvas<sup>2</sup>, C. Robert<sup>2</sup>, T.Quynh Truong Hoang<sup>3</sup> and F. Martinez-Hergueta<sup>1</sup>

<sup>1</sup>*School of Engineering, Institute for Infrastructure and Environment, University of Edinburgh, UK*

<sup>2</sup>*School of Engineering, Institute for Materials and Processes, University of Edinburgh, UK*

<sup>3</sup>*ESTACA, Pôle Mécanique des Structures Composites et Environnement, Ecole d'ingénieurs, France*

3D printing has become a widespread technology to design complex geometries [1]. There are numerous methods that allow to implement the 3D printing process [2]. Among them Fused Deposition Modelling (FDM) is a common technique using filaments made by different materials such as thermoplastic, metal, wood or composite [3]. The emergence of conductive filaments made of carbon particles reinforced thermoplastic allows to print integrated electrical circuits on 3D parts. Some studies have been done on the electrical properties of conductive filament [4] including self-heating [5], however the electrical properties once the glass transition temperature ( $T_g$ ) is overtaken by Joule's heating have not been studied.

In this project the influence of the printing parameters (e.g. layer height, printing direction, nozzle diameter) on the mechanical and electrical properties of carbon particles reinforced PLA has been studied. A ductile mechanical behaviour has been exhibited in the thinner layer height sample while the bigger layer heights showed a brittle fracture. The degree of crystallinity of printed samples has been measured by DSC to explain the difference in fracture behaviour between the samples printed with different layer heights. A thermodynamic simulation has been carried out to find the temperature profile and to determine the cooling rate of the deposited filaments. The results illustrate that the thinner layer height cools faster after extrusion and do not reheat significantly the previous deposited layer. Difference in electrical properties have also been shown according to the printing direction and heating method. A more reliable electrical behaviour is revealed in the 0° printing direction sample than in 90° sample and a bigger increase of resistance when heated by oven is observed.

### REFERENCES

- [1] Wang, Xin, et al. "3D printing of polymer matrix composites: A review and prospective." *Composites Part B: Engineering* 110 (2017): 442-458.
- [2] Ngo, Tuan D., et al. "Additive manufacturing (3D printing): A review of materials, methods, applications and challenges." *Composites Part B: Engineering* 143 (2018): 172-196
- [3] Dudek, P. F. D. M. "FDM 3D printing technology in manufacturing composite elements." *Archives of metallurgy and materials* 58.4 (2013): 1415-1418.
- [4] Gnanasekaran, Karthikeyan, et al. "3D printing of CNT-and graphene-based conductive polymer nanocomposites by fused deposition modeling." *Applied materials today* 9 (2017):21-28.
- [5] Tirado-Garcia, I., et al. "Conductive 3D printed PLA composites: On the interplay of mechanical, electrical and thermal behaviours." *Composite Structures* 265 (2021): 113744.